



PELLET



WOOD



THERMO



SICURO TOP
INSIDE



17,3 kW
12,3 kW



11,2 kW
6,5 kW



4,8 kW
4,8 kW

η

93 %
91,9 %



TOP EXIT
PELLET
WOOD

PRODUKTDDETAILS



A

			PELLET	WOOD
Nennwärmeleistung Nominal heat output	Pmin-Pmax	kg/h	4,7-16,1	11,3
Pellet-Holzverbrauch Pellet-logs consumption	Pmin-Pmax	kg/h	1-3,5	2,8
Betriebsautonomie Operation autonomy	Pmin-Pmax	h	30-9	-
Tankkapazität Tank capacity		kg	30	-
Rauchabzug Exhaust flue		Ø	180	

Maximale Leistung bei Volllast.
Maximum power obtainable with full load.

Alle hydraulischen Komponenten serienmäßig

Beschichtung aus lackiertem Stahl und hochwertiger Majolika

Einstellbare Luftzufuhr für Holz mit thermostatischem Ventil

Sicherheitsdichtung aus Edelstahl

„Kalte“ Türgriff

Feuertür mit doppeltem Keramikglas

All plumbing components as standard supply

Covering in painted steel and majolica at the top

Wood combustion air regulation with thermostatic valve

Safety seal in stainless steel

“Cold” door handle

Fire door with double ceramic glazing

116

CODE • CODE

DH

Heizofen DUAL

P

Sanitär-Kit
Sanitary kit

ZUBEHÖR • OPTIONAL

BESCHREIBUNG • DESCRIPTION

MODULO.WIFI2.0

Modul zur Wi-Fi-Steuerung
Wi-Fi device

FARBEN • COLORS



AVORIO



TERRA DI SIENA



BORDEAUX



MATT BLACK